



HiHero

HIGH EFFICIENCY HETEROJUNCTION CELL TECHNOLOGY

405 W ~ 430 W

CS6R-405 | 410 | 415 | 420 | 425 | 430H-AG

Dimensions: 1727 × 1134 × 35 mm (68.0 × 44.6 × 1.38 in)

Weight: 23.0 kg (50.7 lbs)

Max. System Voltage: 1500 V (IEC) or 1000 V (IEC)

* Silver frame product can be provided upon request.

MORE POWER



Module efficiency up to 22.0%, maximize the use of rooftop space



No BO-LID, excellent anti-LeTID & anti-PID performance. Low power degradation, high energy yield



Leading temperature coefficient (Pmax): $-0.26\%/^{\circ}\text{C}$, increases energy yield in hot climate



Better shading tolerance

MORE RELIABLE



Minimizes micro-crack impacts



Heavy snow load up to 5400 Pa, enhanced wind load up to 2400 Pa*

* For detailed information, please refer to the Installation Manual.



Industry Leading Product Warranty on Materials and Workmanship*



Linear Power Performance Warranty*

*According to the applicable Canadian Solar Limited Warranty Statement.

MANAGEMENT SYSTEM CERTIFICATES*

ISO 9001:2015 / Quality management system
ISO 14001:2015 / Standards for environmental management system
ISO 45001: 2018 / International standards for occupational health & safety

PRODUCT CERTIFICATES*

* The specific certificates applicable to different module types and markets will vary, and therefore not all of the certifications listed herein will simultaneously apply to the products you order or use. Please contact your local Canadian Solar sales representative to confirm the specific certificates available for your Product and applicable in the regions in which the products will be used.

CSI Solar Co., Ltd. is committed to providing high quality solar products, solar system solutions and services to customers around the world. Canadian Solar was recognized as the No. 1 module supplier for quality and performance/price ratio in the IHS Module Customer Insight Survey, and is a leading PV project developer and manufacturer of solar modules, with over 55 GW deployed around the world since 2001.